



- ① FINISH SURFACE OF MULCH (3" THICK)
- ② 6" ROUND VALVE BOX. SEE NOTE BELOW
- ③ AIR / VACUUM RELIEF VALVE
- ④ 3/4" M x 1/2" F REDUCTION BUSHING
- ⑤ DRIPPERLINE COMBINATION TEE (1/2" x 1/2" x 3/4" FPT)
- ⑥ 3/4" GRAVEL SUMP
- ⑦ DRIPPERLINE TUBING: FROM SURFACE INTO BOX TYPICAL
- ⑧ SOIL SURFACE FINISH GRADE, 3"-4" COVER OVER PIPE
- ⑨ 1/4" GALVANIZED WIRE MESH

**NOTE:**

TOP OF VALVE BOX TO BE INSTALLED 3" ABOVE FINISH GRADE IN PLANTER AREAS, AND EVEN WITH FINISH SURFACE OF MULCH.

SPECIAL DISTRICTS/ PARKS AND COMMUNITY SERVICES	DATE	1/12	<h2 style="margin: 0;">CITY OF MORENO VALLEY</h2> <p style="margin: 0; font-size: small;">PREPARED BY CAPITAL PROJECTS</p>	
APPROVED BY  	DIVISION MANAGER INITIAL  	<h3 style="margin: 0;">AIR / VACUUM RELIEF VALVE (FOR DRIPPERLINE)</h3>		6 of 6  NO. <h3 style="margin: 0;">562F</h3>
DEPUTY PUBLIC WORKS DIRECTOR/ ACTING CITY ENGINEER				